

ECONOMICAL & EXCELLENCE
IN HOLE MAKING



Solid Carbide Drills

EcoCut Machining Solutions



COMPANY PROFILE

EcoCut Machining Solutions was established in the year 2011 at Bengaluru, India. We are the leading Manufacturer, Exporter, wholesaler, supplier and trader of Expandable Cermet, PCD and CBN Reamers, Solid Carbide Reamers, Solid Carbide Drills, End Mills, Special Profile Cutting Tools, Anti Vibration Tools, Ceramic, PCD and CBN Inserts, Deep Hole Drilling Tools and Tool Holders. We Manufacture and procure these products from our certified and reliable vendors. Our vendors use quality assured material and advanced technology in the production process of these goods. With their consistent support, we are able to provide highly reliable, quality assured and maintenance free tools and equipment to our esteem customers in bulk with timely delivery. We provide these products to our customers according to their demands and the specifications given by them in order to attain their maximum satisfaction.

We are a client oriented company and that's why we perform all the business activities by keeping their needs and expectations from us in our mind. Their complete satisfaction is our primary objective and we can do every possible thing to satisfy them completely. Our client centric approach and policies are the proof of our devotion and dedication towards our customers.

Today, EcoCut Machining Solutions is backed by a huge client base and this is our actual achievement. This is possible due to the supervision of our respected director Mr. Balajee Adapa. He is highly experienced and dedicated towards his profession and responsibilities. His contribution is precious and an important reason behind our success and achievements. Besides this, our employees are also very talented and hard working at the same time. With their support, we have been providing best quality tools and equipment to our patrons since the time of our incorporation.


EcoCut Machining Solutions

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITHOUT INTERNAL COOLANT (3 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	Non Through Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
3	SFP203W-0300-4	62	20	28	4	P/S/K/S
3.1	SFP203W-0310-4	62	20	28	4	P/S/K/S
3.17(1/8)	SFP203W-0317-4	62	20	28	4	P/S/K/S
3.2	SFP203W-0320-4	62	20	28	4	P/S/K/S
3.3	SFP203W-0330-4	62	20	28	4	P/S/K/S
3.4	SFP203W-0340-4	62	20	28	4	P/S/K/S
3.5	SFP203W-0350-4	62	20	28	4	P/S/K/S
3.57(9/64)	SFP203W-0357-4	62	20	28	4	P/S/K/S
3.6	SFP203W-0360-4	62	20	28	4	P/S/K/S
3.7	SFP203W-0370-4	62	20	28	4	P/S/K/S
3.8	SFP203W-0380-4	66	24	28	4	P/S/K/S
3.9	SFP203W-0390-4	66	24	28	4	P/S/K/S
3.97(5/32)	SFP203W-0397-4	66	24	28	4	P/S/K/S
4	SFP203W-0400-4	66	24	28	4	P/S/K/S
4.1	SFP203W-0410-6	66	24	28	6	P/S/K/S
4.2	SFP203W-0420-6	66	24	36	6	P/S/K/S
4.3	SFP203W-0430-6	66	24	36	6	P/S/K/S
4.37(11/64)	SFP203W-0437-6	66	24	36	6	P/S/K/S
4.4	SFP203W-0440-6	66	24	36	6	P/S/K/S
4.5	SFP203W-0450-6	66	24	36	6	P/S/K/S
4.6	SFP203W-0460-6	66	24	36	6	P/S/K/S
4.7	SFP203W-0470-6	66	24	36	6	P/S/K/S
4.76(3/16)	SFP203W-0476-6	66	28	36	6	P/S/K/S
4.8	SFP203W-0480-6	66	28	36	6	P/S/K/S
4.9	SFP203W-0490-6	66	28	36	6	P/S/K/S
5	SFP203W-0500-6	66	28	36	6	P/S/K/S
5.1	SFP203W-0510-6	66	28	36	6	P/S/K/S
5.16(13/64)	SFP203W-0516-6	66	28	36	6	P/S/K/S
5.2	SFP203W-0520-6	66	28	36	6	P/S/K/S
5.3	SFP203W-0530-6	66	28	36	6	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITHOUT INTERNAL COOLANT (3 L/D)



d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	Non Through Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
5.4	SFP203W-0540-6	66	28	36	6	P/S/K/S
5.5	SFP203W-0550-6	66	28	36	6	P/S/K/S
5.56(7/32)	SFP203W-0556-6	66	28	36	6	P/S/K/S
5.6	SFP203W-0560-6	66	28	36	6	P/S/K/S
5.7	SFP203W-0570-6	66	28	36	6	P/S/K/S
5.8	SFP203W-0580-6	66	28	36	6	P/S/K/S
5.9	SFP203W-0590-6	66	28	36	6	P/S/K/S
5.95(15/64)	SFP203W-0595-6	66	28	36	6	P/S/K/S
6	SFP203W-0600-6	66	28	36	6	P/S/K/S
6.1	SFP203W-0610-8	79	34	36	8	P/S/K/S
6.2	SFP203W-0620-8	79	34	36	8	P/S/K/S
6.3	SFP203W-0630-8	79	34	36	8	P/S/K/S
6.35(1/4)	SFP203W-0635-8	79	34	36	8	P/S/K/S
6.4	SFP203W-0640-8	79	34	36	8	P/S/K/S
6.5	SFP203W-0650-8	79	34	36	8	P/S/K/S
6.6	SFP203W-0660-8	79	34	36	8	P/S/K/S
6.7	SFP203W-0670-8	79	34	36	8	P/S/K/S
6.75(17/64)	SFP203W-0675-8	79	34	36	8	P/S/K/S
6.8	SFP203W-0680-8	79	34	36	8	P/S/K/S
6.9	SFP203W-0690-8	79	34	36	8	P/S/K/S
7	SFP203W-0700-8	79	34	36	8	P/S/K/S
7.1	SFP203W-0710-8	79	34	36	8	P/S/K/S
7.14(9/32)	SFP203W-0714-8	79	41	36	8	P/S/K/S
7.2	SFP203W-0720-8	79	41	36	8	P/S/K/S
7.3	SFP203W-0730-8	79	41	36	8	P/S/K/S
7.4	SFP203W-0740-8	79	41	36	8	P/S/K/S
7.5	SFP203W-0750-8	79	41	36	8	P/S/K/S
7.54(19/64)	SFP203W-0754-8	79	41	36	8	P/S/K/S
7.6	SFP203W-0760-8	79	41	36	8	P/S/K/S
7.7	SFP203W-0770-8	79	41	36	8	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITHOUT INTERNAL COOLANT (3 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	Non Through Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
7.8	SFP203W-0780-8	79	41	36	8	P/S/K/S
7.9	SFP203W-0790-8	79	41	36	8	P/S/K/S
7.94(5/16)	SFP203W-0794-8	79	41	36	8	P/S/K/S
8	SFP203W-0800-8	79	41	36	8	P/S/K/S
8.1	SFP203W-0810-10	89	47	40	10	P/S/K/S
8.2	SFP203W-0820-10	89	47	40	10	P/S/K/S
8.3	SFP203W-0820-10	89	47	40	10	P/S/K/S
8.33(21/64)	SFP203W-0833-10	89	47	40	10	P/S/K/S
8.4	SFP203W-0840-10	89	47	40	10	P/S/K/S
8.5	SFP203W-0850-10	89	47	40	10	P/S/K/S
8.6	SFP203W-0860-10	89	47	40	10	P/S/K/S
8.7	SFP203W-0870-10	89	47	40	10	P/S/K/S
8.73(11/32)	SFP203W-0873-10	89	47	40	10	P/S/K/S
8.8	SFP203W-0880-10	89	47	40	10	P/S/K/S
8.9	SFP203W-0890-10	89	47	40	10	P/S/K/S
9	SFP203W-0900-10	89	47	40	10	P/S/K/S
9.1	SFP203W-0910-10	89	47	40	10	P/S/K/S
9.13(23/64)	SFP203W-0913-10	89	47	40	10	P/S/K/S
9.2	SFP203W-0920-10	89	47	40	10	P/S/K/S
9.3	SFP203W-0930-10	89	47	40	10	P/S/K/S
9.4	SFP203W-0940-10	89	47	40	10	P/S/K/S
9.5	SFP203W-0950-10	89	47	40	10	P/S/K/S
9.52(3/8)	SFP203W-0952-10	89	47	40	10	P/S/K/S
9.6	SFP203W-0960-10	89	47	40	10	P/S/K/S
9.7	SFP203W-0970-10	89	47	40	10	P/S/K/S
9.8	SFP203W-0980-10	89	47	40	10	P/S/K/S
9.9	SFP203W-0990-10	89	47	40	10	P/S/K/S
9.92(25/64)	SFP203W-0992-10	89	47	40	10	P/S/K/S
10	SFP203W-1000-10	89	47	40	10	P/S/K/S
10.1	SFP203W-1010-12	102	55	45	12	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITHOUT INTERNAL COOLANT (3 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	Non Through Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
10.2	SFP203W-1020-12	102	55	45	12	P/S/K/S
10.3	SFP203W-1030-12	102	55	45	12	P/S/K/S
10.32(13/32)	SFP203W-1032-12	102	55	45	12	P/S/K/S
10.4	SFP203W-1040-12	102	55	45	12	P/S/K/S
10.5	SFP203W-1050-12	102	55	45	12	P/S/K/S
10.6	SFP203W-1060-12	102	55	45	12	P/S/K/S
10.7	SFP203W-1070-12	102	55	45	12	P/S/K/S
10.8	SFP203W-1080-12	102	55	45	12	P/S/K/S
10.9	SFP203W-1090-12	102	55	45	12	P/S/K/S
11	SFP203W-1100-12	102	55	45	12	P/S/K/S
11.1	SFP203W-1110-12	102	55	45	12	P/S/K/S
11.11(7/16)	SFP203W-1111-12	102	55	45	12	P/S/K/S
11.2	SFP203W-1120-12	102	55	45	12	P/S/K/S
11.3	SFP203W-1130-12	102	55	45	12	P/S/K/S
11.4	SFP203W-1140-12	102	55	45	12	P/S/K/S
11.5	SFP203W-1150-12	102	55	45	12	P/S/K/S
11.6	SFP203W-1160-12	102	55	45	12	P/S/K/S
11.7	SFP203W-1170-12	102	55	45	12	P/S/K/S
11.8	SFP203W-1180-12	102	55	45	12	P/S/K/S
11.9	SFP203W-1190-12	102	55	45	12	P/S/K/S
11.91(15/32)	SFP203W-1191-12	102	55	45	12	P/S/K/S
12	SFP203W-1200-12	102	55	45	12	P/S/K/S
12.1	SFP203W-1210-14	107	60	45	14	P/S/K/S
12.2	SFP203W-1220-14	107	60	45	14	P/S/K/S
12.3	SFP203W-1230-14	107	60	45	14	P/S/K/S
12.4	SFP203W-1240-14	107	60	45	14	P/S/K/S
12.5	SFP203W-1250-14	107	60	45	14	P/S/K/S
12.6	SFP203W-1260-14	107	60	45	14	P/S/K/S
12.7(1/2)	SFP203W-1270-14	107	60	45	14	P/S/K/S
12.8	SFP203W-1280-14	107	60	45	14	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITHOUT INTERNAL COOLANT (3 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	Non Through Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
12.9	SFP203W-1290-14	107	60	45	14	P/S/K/S
13	SFP203W-1300-14	107	60	45	14	P/S/K/S
13.1	SFP203W-1310-14	107	60	45	14	P/S/K/S
13.2	SFP203W-1320-14	107	60	45	14	P/S/K/S
13.3	SFP203W-1330-14	107	60	45	14	P/S/K/S
13.4	SFP203W-1340-14	107	60	45	14	P/S/K/S
13.5	SFP203W-1350-14	107	60	45	14	P/S/K/S
13.6	SFP203W-1360-14	107	60	45	14	P/S/K/S
13.7	SFP203W-1370-14	107	60	45	14	P/S/K/S
13.8	SFP203W-1380-14	107	60	45	14	P/S/K/S
13.9	SFP203W-1390-14	107	60	45	14	P/S/K/S
14	SFP203W-1400-14	107	60	45	14	P/S/K/S
14.1	SFP203W-1410-16	115	65	48	16	P/S/K/S
14.2	SFP203W-1420-16	115	65	48	16	P/S/K/S
14.29(9/16)	SFP203W-1429-16	115	65	48	16	P/S/K/S
14.3	SFP203W-1430-16	115	65	48	16	P/S/K/S
14.4	SFP203W-1440-16	115	65	48	16	P/S/K/S
14.5	SFP203W-1450-16	115	65	48	16	P/S/K/S
14.6	SFP203W-1460-16	115	65	48	16	P/S/K/S
14.7	SFP203W-1470-16	115	65	48	16	P/S/K/S
14.8	SFP203W-1480-16	115	65	48	16	P/S/K/S
14.9	SFP203W-1490-16	115	65	48	16	P/S/K/S
15	SFP203W-1500-16	115	65	48	16	P/S/K/S
15.1	SFP203W-1510-16	115	65	48	16	P/S/K/S
15.2	SFP203W-1520-16	115	65	48	16	P/S/K/S
15.3	SFP203W-1530-16	115	65	48	16	P/S/K/S
15.4	SFP203W-1540-16	115	65	48	16	P/S/K/S
15.5	SFP203W-1550-16	115	65	48	16	P/S/K/S
15.6	SFP203W-1560-16	115	65	48	16	P/S/K/S
15.7	SFP203W-1570-16	115	65	48	16	P/S/K/S
15.8	SFP203W-1580-16	115	65	48	16	P/S/K/S
15.9	SFP203W-1590-16	115	65	48	16	P/S/K/S
16	SFP203W-1600-16	115	65	48	16	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITH INTERNAL COOLANT (3 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
3	SFP203N-0300-4	62	20	28	4	P/S/K/S
3.1	SFP203N-0310-4	62	20	28	4	P/S/K/S
3.17 (1/8)	SFP203N-0317-4	62	20	28	4	P/S/K/S
3.2	SFP203N-0320-4	62	20	28	4	P/S/K/S
3.3	SFP203N-0330-4	62	20	28	4	P/S/K/S
3.4	SFP203N-0340-4	62	20	28	4	P/S/K/S
3.5	SFP203N-0350-4	62	20	28	4	P/S/K/S
3.57 (9/64)	SFP203N-0357-4	62	20	28	4	P/S/K/S
3.6	SFP203N-0360-4	62	20	28	4	P/S/K/S
3.7	SFP203N-0370-4	62	20	28	4	P/S/K/S
3.8	SFP203N-0380-4	66	24	28	4	P/S/K/S
3.9	SFP203N-0390-4	66	24	28	4	P/S/K/S
3.97 (5/32)	SFP203N-0397-4	66	24	28	4	P/S/K/S
4	SFP203N-0400-4	66	24	28	4	P/S/K/S
4.1	SFP203N-0410-6	66	24	36	6	P/S/K/S
4.2	SFP203N-0420-6	66	24	36	6	P/S/K/S
4.3	SFP203N-0430-6	66	24	36	6	P/S/K/S
4.37 (11/64)	SFP203N-0437-6	66	24	36	6	P/S/K/S
4.4	SFP203N-0440-6	66	24	36	6	P/S/K/S
4.5	SFP203N-0450-6	66	24	36	6	P/S/K/S
4.6	SFP203N-0460-6	66	24	36	6	P/S/K/S
4.7	SFP203N-0470-6	66	24	36	6	P/S/K/S
4.76 (3/16)	SFP203N-0476-6	66	28	36	6	P/S/K/S
4.8	SFP203N-0480-6	66	28	36	6	P/S/K/S
4.9	SFP203N-0490-6	66	28	36	6	P/S/K/S
5	SFP203N-0500-6	66	28	36	6	P/S/K/S
5.1	SFP203N-0510-6	66	28	36	6	P/S/K/S
5.16 (13/64)	SFP203N-0516-6	66	28	36	6	P/S/K/S
5.2	SFP203N-0520-6	66	28	36	6	P/S/K/S
5.3	SFP203N-0530-6	66	28	36	6	P/S/K/S
5.4	SFP203N-0540-6	66	28	36	6	P/S/K/S
5.5	SFP203N-0550-6	66	28	36	6	P/S/K/S
5.56 (7/32)	SFP203N-0556-6	66	28	36	6	P/S/K/S
5.6	SFP203N-0560-6	66	28	36	6	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITH INTERNAL COOLANT (3 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
5.7	SFP203N-0570-6	66	28	36	6	P/S/K/S
5.8	SFP203N-0580-6	66	28	36	6	P/S/K/S
5.9	SFP203N-0590-6	66	28	36	6	P/S/K/S
5.95 (15/64)	SFP203N-0595-6	66	28	36	6	P/S/K/S
6	SFP203N-0600-6	66	28	36	6	P/S/K/S
6.1	SFP203N-0610-8	79	34	36	8	P/S/K/S
6.2	SFP203N-0620-8	79	34	36	8	P/S/K/S
6.3	SFP203N-0630-8	79	34	36	8	P/S/K/S
6.35 (1/4)	SFP203N-0635-8	79	34	36	8	P/S/K/S
6.4	SFP203N-0640-8	79	34	36	8	P/S/K/S
6.5	SFP203N-0650-8	79	34	36	8	P/S/K/S
6.6	SFP203N-0660-8	79	34	36	8	P/S/K/S
6.7	SFP203N-0670-8	79	34	36	8	P/S/K/S
6.75 (17/64)	SFP203N-0675-8	79	34	36	8	P/S/K/S
6.8	SFP203N-0680-8	79	34	36	8	P/S/K/S
6.9	SFP203N-0690-8	79	34	36	8	P/S/K/S
7	SFP203N-0700-8	79	34	36	8	P/S/K/S
7.1	SFP203N-0710-8	79	34	36	8	P/S/K/S
7.14 (9/32)	SFP203N-0714-8	79	41	36	8	P/S/K/S
7.2	SFP203N-0720-8	79	41	36	8	P/S/K/S
7.3	SFP203N-0730-8	79	41	36	8	P/S/K/S
7.4	SFP203N-0740-8	79	41	36	8	P/S/K/S
7.5	SFP203N-0750-8	79	41	36	8	P/S/K/S
7.54 (19/64)	SFP203N-0754-8	79	41	36	8	P/S/K/S
7.6	SFP203N-0760-8	79	41	36	8	P/S/K/S
7.7	SFP203N-0770-8	79	41	36	8	P/S/K/S
7.8	SFP203N-0780-8	79	41	36	8	P/S/K/S
7.9	SFP203N-0790-8	79	41	36	8	P/S/K/S
7.94 (5/16)	SFP203N-0794-8	79	41	36	8	P/S/K/S
8	SFP203N-0800-8	79	41	36	8	P/S/K/S
8.1	SFP203N-0810-10	89	47	40	10	P/S/K/S
8.2	SFP203N-0820-10	89	47	40	10	P/S/K/S
8.3	SFP203N-0820-10	89	47	40	10	P/S/K/S
8.33 (21/64)	SFP203N-0833-10	89	47	40	10	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITH INTERNAL COOLANT (3 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
8.4	SFP203N-0840-10	89	47	40	10	P/S/K/S
8.5	SFP203N-0850-10	89	47	40	10	P/S/K/S
8.6	SFP203N-0860-10	89	47	40	10	P/S/K/S
8.7	SFP203N-0870-10	89	47	40	10	P/S/K/S
8.73 (11/32)	SFP203N-0873-10	89	47	40	10	P/S/K/S
8.8	SFP203N-0880-10	89	47	40	10	P/S/K/S
8.9	SFP203N-0890-10	89	47	40	10	P/S/K/S
9	SFP203N-0900-10	89	47	40	10	P/S/K/S
9.1	SFP203N-0910-10	89	47	40	10	P/S/K/S
9.13 (23/64)	SFP203N-0913-10	89	47	40	10	P/S/K/S
9.2	SFP203N-0920-10	89	47	40	10	P/S/K/S
9.3	SFP203N-0930-10	89	47	40	10	P/S/K/S
9.4	SFP203N-0940-10	89	47	40	10	P/S/K/S
9.5	SFP203N-0950-10	89	47	40	10	P/S/K/S
9.52 (3/8)	SFP203N-0952-10	89	47	40	10	P/S/K/S
9.6	SFP203N-0960-10	89	47	40	10	P/S/K/S
9.7	SFP203N-0970-10	89	47	40	10	P/S/K/S
9.8	SFP203N-0980-10	89	47	40	10	P/S/K/S
9.9	SFP203N-0990-10	89	47	40	10	P/S/K/S
9.92 (25/64)	SFP203N-0992-10	89	47	40	10	P/S/K/S
10	SFP203N-1000-10	89	47	40	10	P/S/K/S
10.1	SFP203N-1010-12	102	55	45	12	P/S/K/S
10.2	SFP203N-1020-12	102	55	45	12	P/S/K/S
10.3	SFP203N-1030-12	102	55	45	12	P/S/K/S
10.32 (13/32)	SFP203N-1032-12	102	55	45	12	P/S/K/S
10.4	SFP203N-1040-12	102	55	45	12	P/S/K/S
10.5	SFP203N-1050-12	102	55	45	12	P/S/K/S
10.6	SFP203N-1060-12	102	55	45	12	P/S/K/S
10.7	SFP203N-1070-12	102	55	45	12	P/S/K/S
10.8	SFP203N-1080-12	102	55	45	12	P/S/K/S
10.9	SFP203N-1090-12	102	55	45	12	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITH INTERNAL COOLANT (3 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
11	SFP203N-1100-12	102	55	45	12	P/S/K/S
11.1	SFP203N-1110-12	102	55	45	12	P/S/K/S
11.11 (7/16)	SFP203N-1111-12	102	55	45	12	P/S/K/S
11.2	SFP203N-1120-12	102	55	45	12	P/S/K/S
11.3	SFP203N-1130-12	102	55	45	12	P/S/K/S
11.4	SFP203N-1140-12	102	55	45	12	P/S/K/S
11.5	SFP203N-1150-12	102	55	45	12	P/S/K/S
11.6	SFP203N-1160-12	102	55	45	12	P/S/K/S
11.7	SFP203N-1170-12	102	55	45	12	P/S/K/S
11.8	SFP203N-1180-12	102	55	45	12	P/S/K/S
11.9	SFP203N-1190-12	102	55	45	12	P/S/K/S
11.91 (15/32)	SFP203N-1191-12	102	55	45	12	P/S/K/S
12	SFP203N-1200-12	102	55	45	12	P/S/K/S
12.1	SFP203N-1210-14	107	60	45	14	P/S/K/S
12.2	SFP203N-1220-14	107	60	45	14	P/S/K/S
12.3	SFP203N-1230-14	107	60	45	14	P/S/K/S
12.4	SFP203N-1240-14	107	60	45	14	P/S/K/S
12.5	SFP203N-1250-14	107	60	45	14	P/S/K/S
12.6	SFP203N-1260-14	107	60	45	14	P/S/K/S
12.7 (1/2)	SFP203N-1270-14	107	60	45	14	P/S/K/S
12.8	SFP203N-1280-14	107	60	45	14	P/S/K/S
12.9	SFP203N-1290-14	107	60	45	14	P/S/K/S
13	SFP203N-1300-14	107	60	45	14	P/S/K/S
13.1	SFP203N-1310-14	107	60	45	14	P/S/K/S
13.2	SFP203N-1320-14	107	60	45	14	P/S/K/S
13.3	SFP203N-1330-14	107	60	45	14	P/S/K/S
13.4	SFP203N-1340-14	107	60	45	14	P/S/K/S
13.5	SFP203N-1350-14	107	60	45	14	P/S/K/S
13.6	SFP203N-1360-14	107	60	45	14	P/S/K/S
13.7	SFP203N-1370-14	107	60	45	14	P/S/K/S
13.8	SFP203N-1380-14	107	60	45	14	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITH INTERNAL COOLANT (3 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
13.9	SFP203N-1390-14	107	60	45	14	P/S/K/S
14	SFP203N-1400-14	107	60	45	14	P/S/K/S
14.1	SFP203N-1410-16	115	65	48	16	P/S/K/S
14.2	SFP203N-1420-16	115	65	48	16	P/S/K/S
14.29 (9/16)	SFP203N-1429-16	115	65	48	16	P/S/K/S
14.3	SFP203N-1430-16	115	65	48	16	P/S/K/S
14.4	SFP203N-1440-16	115	65	48	16	P/S/K/S
14.5	SFP203N-1450-16	115	65	48	16	P/S/K/S
14.6	SFP203N-1460-16	115	65	48	16	P/S/K/S
14.7	SFP203N-1470-16	115	65	48	16	P/S/K/S
14.8	SFP203N-1480-16	115	65	48	16	P/S/K/S
14.9	SFP203N-1490-16	115	65	48	16	P/S/K/S
15	SFP203N-1500-16	115	65	48	16	P/S/K/S
15.1	SFP203N-1510-16	115	65	48	16	P/S/K/S
15.2	SFP203N-1520-16	115	65	48	16	P/S/K/S
15.3	SFP203N-1530-16	115	65	48	16	P/S/K/S
15.4	SFP203N-1540-16	115	65	48	16	P/S/K/S
15.5	SFP203N-1550-16	115	65	48	16	P/S/K/S
15.6	SFP203N-1560-16	115	65	48	16	P/S/K/S
15.7	SFP203N-1570-16	115	65	48	16	P/S/K/S
15.8	SFP203N-1580-16	115	65	48	16	P/S/K/S
15.9	SFP203N-1590-16	115	65	48	16	P/S/K/S
16	SFP203N-1600-16	115	65	48	16	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITHOUT INTERNAL COOLANT (5 L/D)



d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
3	SFP205W-0300-4	62	28	28	4	P/S/K/S
3.1	SFP205W-0310-4	62	28	28	4	P/S/K/S
3.17 (1/8)	SFP205W-0317-4	62	28	28	4	P/S/K/S
3.2	SFP205W-0320-4	62	28	28	4	P/S/K/S
3.3	SFP205W-0330-4	62	28	28	4	P/S/K/S
3.4	SFP205W-0340-4	62	28	28	4	P/S/K/S
3.5	SFP205W-0350-4	62	28	28	4	P/S/K/S
3.57(9/64)	SFP205W-0357-4	62	28	28	4	P/S/K/S
3.6	SFP205W-0360-4	62	28	28	4	P/S/K/S
3.7	SFP205W-0370-4	62	28	28	4	P/S/K/S
3.8	SFP205W-0380-4	62	28	28	4	P/S/K/S
3.9	SFP205W-0390-4	62	28	28	4	P/S/K/S
3.97(5/32)	SFP205W-0397-4	62	28	28	4	P/S/K/S
4	SFP205W-0400-4	62	28	28	4	P/S/K/S
4.1	SFP205W-0410-6	74	36	36	6	P/S/K/S
4.2	SFP205W-0420-6	74	36	36	6	P/S/K/S
4.3	SFP205W-0430-6	74	36	36	6	P/S/K/S
4.37(11/64)	SFP205W-0437-6	74	36	36	6	P/S/K/S
4.4	SFP205W-0440-6	74	36	36	6	P/S/K/S
4.5	SFP205W-0450-6	74	36	36	6	P/S/K/S
4.6	SFP205W-0460-6	74	36	36	6	P/S/K/S
4.7	SFP205W-0470-6	74	36	36	6	P/S/K/S
4.76(3/16)	SFP205W-0476-6	82	44	36	6	P/S/K/S
4.8	SFP205W-0480-6	82	44	36	6	P/S/K/S
4.9	SFP205W-0490-6	82	44	36	6	P/S/K/S
5	SFP205W-0500-6	82	44	36	6	P/S/K/S
5.1	SFP205W-0510-6	82	44	36	6	P/S/K/S
5.16(13/64)	SFP205W-0516-6	82	44	36	6	P/S/K/S
5.2	SFP205W-0520-6	82	44	36	6	P/S/K/S
5.3	SFP205W-0530-6	82	44	36	6	P/S/K/S
5.4	SFP205W-0540-6	82	44	36	6	P/S/K/S
5.5	SFP205W-0550-6	82	44	36	6	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITHOUT INTERNAL COOLANT (5 L/D)



d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
5.56(7/32)	SFP205W-0556-6	82	44	36	6	P/S/K/S
5.6	SFP205W-0560-6	82	44	36	6	P/S/K/S
5.7	SFP205W-0570-6	82	44	36	6	P/S/K/S
5.8	SFP205W-0580-6	82	44	36	6	P/S/K/S
5.9	SFP205W-0590-6	82	44	36	6	P/S/K/S
5.95(15/64)	SFP205W-0595-6	82	44	36	6	P/S/K/S
6	SFP205W-0600-6	82	44	36	6	P/S/K/S
6.1	SFP205W-0610-8	91	53	36	8	P/S/K/S
6.2	SFP205W-0620-8	91	53	36	8	P/S/K/S
6.3	SFP205W-0630-8	91	53	36	8	P/S/K/S
6.35(1/4)	SFP205W-0635-8	91	53	36	8	P/S/K/S
6.4	SFP205W-0640-8	91	53	36	8	P/S/K/S
6.5	SFP205W-0650-8	91	53	36	8	P/S/K/S
6.6	SFP205W-0660-8	91	53	36	8	P/S/K/S
6.7	SFP205W-0670-8	91	53	36	8	P/S/K/S
6.75(17/64)	SFP205W-0675-8	91	53	36	8	P/S/K/S
6.8	SFP205W-0680-8	91	53	36	8	P/S/K/S
6.9	SFP205W-0690-8	91	53	36	8	P/S/K/S
7	SFP205W-0700-8	91	53	36	8	P/S/K/S
7.1	SFP205W-0710-8	91	53	36	8	P/S/K/S
7.14(9/32)	SFP205W-0714-8	91	53	36	8	P/S/K/S
7.2	SFP205W-0720-8	91	53	36	8	P/S/K/S
7.3	SFP205W-0730-8	91	53	36	8	P/S/K/S
7.4	SFP205W-0740-8	91	53	36	8	P/S/K/S
7.5	SFP205W-0750-8	91	53	36	8	P/S/K/S
7.54(19/64)	SFP205W-0754-8	91	53	36	8	P/S/K/S
7.6	SFP205W-0760-8	91	53	36	8	P/S/K/S
7.7	SFP205W-0770-8	91	53	36	8	P/S/K/S
7.8	SFP205W-0780-8	91	53	36	8	P/S/K/S
7.9	SFP205W-0790-8	91	53	36	8	P/S/K/S
7.94(5/16)	SFP205W-0794-8	91	53	36	8	P/S/K/S
8	SFP205W-0800-8	91	53	36	8	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITHOUT INTERNAL COOLANT (5 L/D)



d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
8.1	SFP205W-0810-10	103	61	40	10	P/S/K/S
8.2	SFP205W-0820-10	103	61	40	10	P/S/K/S
8.3	SFP205W-0820-10	103	61	40	10	P/S/K/S
8.33(21/64)	SFP205W-0833-10	103	61	40	10	P/S/K/S
8.4	SFP205W-0840-10	103	61	40	10	P/S/K/S
8.5	SFP205W-0850-10	103	61	40	10	P/S/K/S
8.6	SFP205W-0860-10	103	61	40	10	P/S/K/S
8.7	SFP205W-0870-10	103	61	40	10	P/S/K/S
8.73(11/32)	SFP205W-0873-10	103	61	40	10	P/S/K/S
8.8	SFP205W-0880-10	103	61	40	10	P/S/K/S
8.9	SFP205W-0890-10	103	61	40	10	P/S/K/S
9	SFP205W-0900-10	103	61	40	10	P/S/K/S
9.1	SFP205W-0910-10	103	61	40	10	P/S/K/S
9.13(23/64)	SFP205W-0913-10	103	61	40	10	P/S/K/S
9.2	SFP205W-0920-10	103	61	40	10	P/S/K/S
9.3	SFP205W-0930-10	103	61	40	10	P/S/K/S
9.4	SFP205W-0940-10	103	61	40	10	P/S/K/S
9.5	SFP205W-0950-10	103	61	40	10	P/S/K/S
9.52(3/8)	SFP205W-0952-10	103	61	40	10	P/S/K/S
9.6	SFP205W-0960-10	103	61	40	10	P/S/K/S
9.7	SFP205W-0970-10	103	61	40	10	P/S/K/S
9.8	SFP205W-0980-10	103	61	40	10	P/S/K/S
9.9	SFP205W-0990-10	103	61	40	10	P/S/K/S
9.92(25/64)	SFP205W-0992-10	103	61	40	10	P/S/K/S
10	SFP205W-1000-10	103	61	40	10	P/S/K/S
10.1	SFP205W-1010-12	118	71	45	12	P/S/K/S
10.2	SFP205W-1020-12	118	71	45	12	P/S/K/S
10.3	SFP205W-1030-12	118	71	45	12	P/S/K/S
10.32(13/32)	SFP205W-1032-12	118	71	45	12	P/S/K/S
10.4	SFP205W-1040-12	118	71	45	12	P/S/K/S
10.5	SFP205W-1050-12	118	71	45	12	P/S/K/S
10.6	SFP205W-1060-12	118	71	45	12	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITHOUT INTERNAL COOLANT (5 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
10.7	SFP205W-1070-12	118	71	45	12	P/S/K/S
10.8	SFP205W-1080-12	118	71	45	12	P/S/K/S
10.9	SFP205W-1090-12	118	71	45	12	P/S/K/S
11	SFP205W-1100-12	118	71	45	12	P/S/K/S
11.1	SFP205W-1110-12	118	71	45	12	P/S/K/S
11.11(7/16)	SFP205W-1111-12	118	71	45	12	P/S/K/S
11.2	SFP205W-1120-12	118	71	45	12	P/S/K/S
11.3	SFP205W-1130-12	118	71	45	12	P/S/K/S
11.4	SFP205W-1140-12	118	71	45	12	P/S/K/S
11.5	SFP205W-1150-12	118	71	45	12	P/S/K/S
11.6	SFP205W-1160-12	118	71	45	12	P/S/K/S
11.7	SFP205W-1170-12	118	71	45	12	P/S/K/S
11.8	SFP205W-1180-12	118	71	45	12	P/S/K/S
11.9	SFP205W-1190-12	118	71	45	12	P/S/K/S
11.91(15/32)	SFP205W-1191-12	118	71	45	12	P/S/K/S
12	SFP205W-1200-12	118	71	45	12	P/S/K/S
12.1	SFP205W-1210-14	124	77	45	14	P/S/K/S
12.2	SFP205W-1220-14	124	77	45	14	P/S/K/S
12.3	SFP205W-1230-14	124	77	45	14	P/S/K/S
12.4	SFP205W-1240-14	124	77	45	14	P/S/K/S
12.5	SFP205W-1250-14	124	77	45	14	P/S/K/S
12.6	SFP205W-1260-14	124	77	45	14	P/S/K/S
12.7(1/2)	SFP205W-1270-14	124	77	45	14	P/S/K/S
12.8	SFP205W-1280-14	124	77	45	14	P/S/K/S
12.9	SFP205W-1290-14	124	77	45	14	P/S/K/S
13	SFP205W-1300-14	124	77	45	14	P/S/K/S
13.1	SFP205W-1310-14	124	77	45	14	P/S/K/S
13.2	SFP205W-1320-14	124	77	45	14	P/S/K/S
13.3	SFP205W-1330-14	124	77	45	14	P/S/K/S
13.4	SFP205W-1340-14	124	77	45	14	P/S/K/S
13.5	SFP205W-1350-14	124	77	45	14	P/S/K/S
13.6	SFP205W-1360-14	124	77	45	14	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITHOUT INTERNAL COOLANT (5 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
13.7	SFP205W-1370-14	124	77	45	14	P/S/K/S
13.8	SFP205W-1380-14	124	77	45	14	P/S/K/S
13.9	SFP205W-1390-14	124	77	45	14	P/S/K/S
14	SFP205W-1400-14	124	77	45	14	P/S/K/S
14.1	SFP205W-1410-16	133	83	48	16	P/S/K/S
14.2	SFP205W-1420-16	133	83	48	16	P/S/K/S
14.29(9/16)	SFP205W-1429-16	133	83	48	16	P/S/K/S
14.3	SFP205W-1430-16	133	83	48	16	P/S/K/S
14.4	SFP205W-1440-16	133	83	48	16	P/S/K/S
14.5	SFP205W-1450-16	133	83	48	16	P/S/K/S
14.6	SFP205W-1460-16	133	83	48	16	P/S/K/S
14.7	SFP205W-1470-16	133	83	48	16	P/S/K/S
14.8	SFP205W-1480-16	133	83	48	16	P/S/K/S
14.9	SFP205W-1490-16	133	83	48	16	P/S/K/S
15	SFP205W-1500-16	133	83	48	16	P/S/K/S
15.1	SFP205W-1510-16	133	83	48	16	P/S/K/S
15.2	SFP205W-1520-16	133	83	48	16	P/S/K/S
15.3	SFP205W-1530-16	133	83	48	16	P/S/K/S
15.4	SFP205W-1540-16	133	83	48	16	P/S/K/S
15.5	SFP205W-1550-16	133	83	48	16	P/S/K/S
15.6	SFP205W-1560-16	133	83	48	16	P/S/K/S
15.7	SFP205W-1570-16	133	83	48	16	P/S/K/S
15.8	SFP205W-1580-16	133	83	48	16	P/S/K/S
15.9	SFP205W-1590-16	133	83	48	16	P/S/K/S
16	SFP205W-1600-16	133	83	48	16	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITH INTERNAL COOLANT (5 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
3	SFP205N-0300-4	62	28	28	4	2949
3.1	SFP205N-0310-4	62	28	28	4	P/S/K/S
3.17 (1/8)	SFP205N-0317-4	62	28	28	4	P/S/K/S
3.2	SFP205N-0320-4	62	28	28	4	P/S/K/S
3.3	SFP205N-0330-4	62	28	28	4	P/S/K/S
3.4	SFP205N-0340-4	62	28	28	4	P/S/K/S
3.5	SFP205N-0350-4	62	28	28	4	P/S/K/S
3.57(9/64)	SFP205N-0357-4	62	28	28	4	P/S/K/S
3.6	SFP205N-0360-4	62	28	28	4	P/S/K/S
3.7	SFP205N-0370-4	62	28	28	4	P/S/K/S
3.8	SFP205N-0380-4	62	28	28	4	P/S/K/S
3.9	SFP205N-0390-4	62	28	28	4	P/S/K/S
3.97(5/32)	SFP205N-0397-4	62	28	28	4	P/S/K/S
4	SFP205N-0400-4	62	28	28	4	P/S/K/S
4.1	SFP205N-0410-6	74	36	36	6	P/S/K/S
4.2	SFP205N-0420-6	74	36	36	6	P/S/K/S
4.3	SFP205N-0430-6	74	36	36	6	P/S/K/S
4.37(11/64)	SFP205N-0437-6	74	36	36	6	P/S/K/S
4.4	SFP205N-0440-6	74	36	36	6	P/S/K/S
4.5	SFP205N-0450-6	74	36	36	6	P/S/K/S
4.6	SFP205N-0460-6	74	36	36	6	P/S/K/S
4.7	SFP205N-0470-6	74	36	36	6	P/S/K/S
4.76(3/16)	SFP205N-0476-6	82	44	36	6	P/S/K/S
4.8	SFP205N-0480-6	82	44	36	6	P/S/K/S
4.9	SFP205N-0490-6	82	44	36	6	P/S/K/S
5	SFP205N-0500-6	82	44	36	6	P/S/K/S
5.1	SFP205N-0510-6	82	44	36	6	P/S/K/S
5.16(13/64)	SFP205N-0516-6	82	44	36	6	P/S/K/S
5.2	SFP205N-0520-6	82	44	36	6	P/S/K/S
5.3	SFP205N-0530-6	82	44	36	6	P/S/K/S
5.4	SFP205N-0540-6	82	44	36	6	P/S/K/S
5.5	SFP205N-0550-6	82	44	36	6	P/S/K/S
5.56(7/32)	SFP205N-0556-6	82	44	36	6	P/S/K/S
5.6	SFP205N-0560-6	82	44	36	6	P/S/K/S
5.7	SFP205N-0570-6	82	44	36	6	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITH INTERNAL COOLANT (5 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
5.8	SFP205N-0580-6	82	44	36	6	P/S/K/S
5.9	SFP205N-0590-6	82	44	36	6	P/S/K/S
5.95(15/64)	SFP205N-0595-6	82	44	36	6	P/S/K/S
6	SFP205N-0600-6	82	44	36	6	P/S/K/S
6.1	SFP205N-0610-8	91	53	36	8	P/S/K/S
6.2	SFP205N-0620-8	91	53	36	8	P/S/K/S
6.3	SFP205N-0630-8	91	53	36	8	P/S/K/S
6.35(1/4)	SFP205N-0635-8	91	53	36	8	P/S/K/S
6.4	SFP205N-0640-8	91	53	36	8	P/S/K/S
6.5	SFP205N-0650-8	91	53	36	8	P/S/K/S
6.6	SFP205N-0660-8	91	53	36	8	P/S/K/S
6.7	SFP205N-0670-8	91	53	36	8	P/S/K/S
6.75(17/64)	SFP205N-0675-8	91	53	36	8	P/S/K/S
6.8	SFP205N-0680-8	91	53	36	8	P/S/K/S
6.9	SFP205N-0690-8	91	53	36	8	P/S/K/S
7	SFP205N-0700-8	91	53	36	8	P/S/K/S
7.1	SFP205N-0710-8	91	53	36	8	P/S/K/S
7.14(9/32)	SFP205N-0714-8	91	53	36	8	P/S/K/S
7.2	SFP205N-0720-8	91	53	36	8	P/S/K/S
7.3	SFP205N-0730-8	91	53	36	8	P/S/K/S
7.4	SFP205N-0740-8	91	53	36	8	P/S/K/S
7.5	SFP205N-0750-8	91	53	36	8	P/S/K/S
7.54(19/64)	SFP205N-0754-8	91	53	36	8	P/S/K/S
7.6	SFP205N-0760-8	91	53	36	8	P/S/K/S
7.7	SFP205N-0770-8	91	53	36	8	P/S/K/S
7.8	SFP205N-0780-8	91	53	36	8	P/S/K/S
7.9	SFP205N-0790-8	91	53	36	8	P/S/K/S
7.94(5/16)	SFP205N-0794-8	91	53	36	8	P/S/K/S
8	SFP205N-0800-8	91	53	36	8	P/S/K/S
8.1	SFP205N-0810-10	103	61	40	10	P/S/K/S
8.2	SFP205N-0820-10	103	61	40	10	P/S/K/S
8.3	SFP205N-0820-10	103	61	40	10	P/S/K/S
8.33(21/64)	SFP205N-0833-10	103	61	40	10	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITH INTERNAL COOLANT (5 L/D)




d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
8.4	SFP205N-0840-10	103	61	40	10	P/S/K/S
8.5	SFP205N-0850-10	103	61	40	10	P/S/K/S
8.6	SFP205N-0860-10	103	61	40	10	P/S/K/S
8.7	SFP205N-0870-10	103	61	40	10	P/S/K/S
8.73(11/32)	SFP205N-0873-10	103	61	40	10	P/S/K/S
8.8	SFP205N-0880-10	103	61	40	10	P/S/K/S
8.9	SFP205N-0890-10	103	61	40	10	P/S/K/S
9	SFP205N-0900-10	103	61	40	10	P/S/K/S
9.1	SFP205N-0910-10	103	61	40	10	P/S/K/S
9.13(23/64)	SFP205N-0913-10	103	61	40	10	P/S/K/S
9.2	SFP205N-0920-10	103	61	40	10	P/S/K/S
9.3	SFP205N-0930-10	103	61	40	10	P/S/K/S
9.4	SFP205N-0940-10	103	61	40	10	P/S/K/S
9.5	SFP205N-0950-10	103	61	40	10	P/S/K/S
9.52(3/8)	SFP205N-0952-10	103	61	40	10	P/S/K/S
9.6	SFP205N-0960-10	103	61	40	10	P/S/K/S
9.7	SFP205N-0970-10	103	61	40	10	P/S/K/S
9.8	SFP205N-0980-10	103	61	40	10	P/S/K/S
9.9	SFP205N-0990-10	103	61	40	10	P/S/K/S
9.92(25/64)	SFP205N-0992-10	103	61	40	10	P/S/K/S
10	SFP205N-1000-10	103	61	40	10	P/S/K/S
10.1	SFP205N-1010-12	118	71	45	12	P/S/K/S
10.2	SFP205N-1020-12	118	71	45	12	P/S/K/S
10.3	SFP205N-1030-12	118	71	45	12	P/S/K/S
10.32(13/32)	SFP205N-1032-12	118	71	45	12	P/S/K/S
10.4	SFP205N-1040-12	118	71	45	12	P/S/K/S
10.5	SFP205N-1050-12	118	71	45	12	P/S/K/S
10.6	SFP205N-1060-12	118	71	45	12	P/S/K/S
10.7	SFP205N-1070-12	118	71	45	12	P/S/K/S
10.8	SFP205N-1080-12	118	71	45	12	P/S/K/S
10.9	SFP205N-1090-12	118	71	45	12	P/S/K/S
11	SFP205N-1100-12	118	71	45	12	P/S/K/S
11.1	SFP205N-1110-12	118	71	45	12	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITH INTERNAL COOLANT (5 L/D)



d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
11.11(7/16)	SFP205N-1111-12	118	71	45	12	P/S/K/S
11.2	SFP205N-1120-12	118	71	45	12	P/S/K/S
11.3	SFP205N-1130-12	118	71	45	12	P/S/K/S
11.4	SFP205N-1140-12	118	71	45	12	P/S/K/S
11.5	SFP205N-1150-12	118	71	45	12	P/S/K/S
11.6	SFP205N-1160-12	118	71	45	12	P/S/K/S
11.7	SFP205N-1170-12	118	71	45	12	P/S/K/S
11.8	SFP205N-1180-12	118	71	45	12	P/S/K/S
11.9	SFP205N-1190-12	118	71	45	12	P/S/K/S
11.91(15/32)	SFP205N-1191-12	118	71	45	12	P/S/K/S
12	SFP205N-1200-12	118	71	45	12	P/S/K/S
12.1	SFP205N-1210-14	124	77	45	14	P/S/K/S
12.2	SFP205N-1220-14	124	77	45	14	P/S/K/S
12.3	SFP205N-1230-14	124	77	45	14	P/S/K/S
12.4	SFP205N-1240-14	124	77	45	14	P/S/K/S
12.5	SFP205N-1250-14	124	77	45	14	P/S/K/S
12.6	SFP205N-1260-14	124	77	45	14	P/S/K/S
12.7(1/2)	SFP205N-1270-14	124	77	45	14	P/S/K/S
12.8	SFP205N-1280-14	124	77	45	14	P/S/K/S
12.9	SFP205N-1290-14	124	77	45	14	P/S/K/S
13	SFP205N-1300-14	124	77	45	14	P/S/K/S
13.1	SFP205N-1310-14	124	77	45	14	P/S/K/S
13.2	SFP205N-1320-14	124	77	45	14	P/S/K/S
13.3	SFP205N-1330-14	124	77	45	14	P/S/K/S
13.4	SFP205N-1340-14	124	77	45	14	P/S/K/S
13.5	SFP205N-1350-14	124	77	45	14	P/S/K/S
13.6	SFP205N-1360-14	124	77	45	14	P/S/K/S
13.7	SFP205N-1370-14	124	77	45	14	P/S/K/S
13.8	SFP205N-1380-14	124	77	45	14	P/S/K/S
13.9	SFP205N-1390-14	124	77	45	14	P/S/K/S
14	SFP205N-1400-14	124	77	45	14	P/S/K/S
14.1	SFP205N-1410-16	133	83	48	16	P/S/K/S
14.2	SFP205N-1420-16	133	83	48	16	P/S/K/S
14.29(9/16)	SFP205N-1429-16	133	83	48	16	P/S/K/S
14.3	SFP205N-1430-16	133	83	48	16	P/S/K/S

HIGH PERFORMANCE SOLID CARBIDE DRILLS WITH INTERNAL COOLANT (5 L/D)



d1 m7(Drill Dia)	Item Code	Over All Length	Flute Length	Shank Length	Shank Dia d2 h6	Materials
d1 (mm)	With Internal Coolant	L1 (mm)	L2 (mm)	L3(mm)	d2 (mm)	P/S/K/S
14.4	SFP205N-1440-16	133	83	48	16	P/S/K/S
14.5	SFP205N-1450-16	133	83	48	16	P/S/K/S
14.6	SFP205N-1460-16	133	83	48	16	P/S/K/S
14.7	SFP205N-1470-16	133	83	48	16	P/S/K/S
14.8	SFP205N-1480-16	133	83	48	16	P/S/K/S
14.9	SFP205N-1490-16	133	83	48	16	P/S/K/S
15	SFP205N-1500-16	133	83	48	16	P/S/K/S
15.1	SFP205N-1510-16	133	83	48	16	P/S/K/S
15.2	SFP205N-1520-16	133	83	48	16	P/S/K/S
15.3	SFP205N-1530-16	133	83	48	16	P/S/K/S
15.4	SFP205N-1540-16	133	83	48	16	P/S/K/S
15.5	SFP205N-1550-16	133	83	48	16	P/S/K/S
15.6	SFP205N-1560-16	133	83	48	16	P/S/K/S
15.7	SFP205N-1570-16	133	83	48	16	P/S/K/S
15.8	SFP205N-1580-16	133	83	48	16	P/S/K/S
15.9	SFP205N-1590-16	133	83	48	16	P/S/K/S
16	SFP205N-1600-16	133	83	48	16	P/S/K/S

EcoCut Machining Solutions

No. 3/1, Ward No. 38, 1st Floor
Sri Muneshwara Industrial Estate
Bengaluru - 560 068 INDIA

Mobile: +91 98456 05577

E-mail: sales@ecocut.in | ecocutms@gmail.com

Authorised Dealer:

